

GSR-16 / GSR-12 Strong Motion Recorder

Features

- Servo Force Balance Accelerometer
- Standard 128 MByte Onboard Memory (Optional up to 2 GByte)
- On-line Diagnostics and Self-Checking System
- LED and LCD Status Indication
- Detailed Analysis Tool with dedicated GeoDAS Data Analysis Package
- Compact and user-friendly
- Quick Installation
- Minimal Maintenance
- Broad Application Field



Outline

The **GSR-12/16** is an acceleration data acquisition system that represents the state of the art technology in earthquake monitoring. In combination with the high performance e.g. Servo (Force Balance) Accelerometer the GSR-12/16 brings a 72/96 dB dynamic range.

The sensor signals are captured by an A/D converter and digitally filtered to increase accuracy and to provide stable performance.

Various parameter settings allow you to configure the **GSR-12/16** very simply and specifically to your desired requirements.

A variety of trigger conditions can be selected to start data capture into a **Solid State Memory Bank** (SRAM) for later analysis. Recorded data can be conveniently transferred to the central station using the serial interface (PC/RS-232 port or modem).

Transferring data to PC while recording is possible and can be done also via modem

Optionally available is the dial-up system that allows the GSR to call automatically a predefined telephone number after an event has been recorded.

A comprehensive package of advanced, menu-driven analysis software is available. **GeoDAS** is included with the **GSR-12/16** and can be used on-site for a first impression of the recorded data. **GeoDAS Data Analysis Package** is a dedicated evaluation program especially designed by **GeoSIG** for earthquake and civil engineering data analysis. It contains all necessary functions and performances for detailed evaluation in the frequency domain functions (FFT, Power Spectrum, Response Spectrum). Additional include integration (acceleration-velocity and velocity-displacement), CAV (Cumulated Absolute Velocity), Space (Rotation, Display) and various data filters.

The **GSR-12/16** is the ideal compact and most cost effective **12 and 16 Bit** approach.

Specifications GSR-16 / GSR-12 Strong Motion Recorder

Set-up and Configuration

All the necessary parameter and configuration settings are selectable with the easy-to-use **GeoDAS** Windows program. The configuration of the **GSR-12/16** is stored in an internal EEPROM which secures the configuration set-up independent of any backup battery requirements.

Data Analysis

The **GeoDAS** program provides basic time history data evaluation in the field. The **GSR-12/16** supplies data available in binary format or as ASCII files. The **GeoDAS Data Analysis Package** covers the requirements of detailed laboratory analysis for most earthquake and civil engineering applications. Any customary in trade evaluation software package can of course be used as well.

Sensor

Various sensors suitable to your application are available. All sensors are housed in a compact case with a single bolt mount, easy to install and to level with three levelling screws. Some sensors can also be built into the **GSR-12/16** unit (internal sensors).

AC-63 Force Balance Accelerometer

Frequency Response: DC to 100 Hz
Largest signal: ± 2 g Std. (± 1 , ± 0.5 g optional)

AC-43 Accelerometer

Frequency Response: DC to 100 Hz
Largest signal: ± 2 g Std. (± 4 , ± 1 , ± 0.5 g optional)

AC-23 Geophone-based Accelerometer

Frequency Response: 0.1 Hz to 50 Hz
Largest signal: ± 2 g Std. (± 1 , ± 0.5 , ± 0.2 g optional)

CMG-5T Gralp™ Accelerometer

Frequency response: DC to 100 Hz
Largest signal: ± 2 g Std. (± 4 , ± 1 , ± 0.5 , 0.1 g optional)

VE-23 Velocity Sensor

Frequency response: 4.5 Hz to 315 Hz
Largest signal: ± 100 mm/s

VE-13 Velocity sensor

Frequency response: 1 Hz to 315 Hz
Largest signal: ± 100 mm/s

Analog Filtering

Antialiasing filter: 6th order Butterworth
Bandwidth: DC to 50 Hz (315 Hz)
Damping: 120 dB / decade
Signal to noise ratio: > 102 dB

Digitiser

A/D Converter: 12 Bit respectively 16 Bit
Least significant bit for 12 Bit: 0.025 % of full scale
Least significant bit for 16 Bit: 0.0015 % of full scale
Sampling rates: 100, 200, 250 SPS
per channel
Bandwidth: 40% of sampling rate

Data Recording

Pre-event-Time: 1 to 20 seconds
Post-event-Time: 1 to 240 seconds
Compression factor: 2.5 typically

Triggering

Level Triggering

Lower band limit: 0.1 Hz (20 dB / decade)
Upper band limit: 12 Hz (40 dB / decade)
Range: 0.1 to 100 % of full scale

STA/LTA Triggering

STA-Base: 0.1 to 10 seconds
LTA-Base: 1 to 100 seconds
STA/LTA-Ratio: 1 to 60 dB

On-Board Memory

Memory: 128 Mbytes Flash Memory
Recording time: 29 minutes per 2 Mbytes
(@ 3 channels, 200 SPS)

Removable ATA memory card (Optional)

Type: PC Card ATA Memory
(PC compatible without additional software)
Size: 128, 256, 512 Mbyte, 1, 2 GByte

Power Supply

Type: Switched power supply
Internal battery: Rechargeable, 12 VDC, 6.5 Ah
Lead battery
Power consumption: 1 W @ 12 VDC typically
Autonomy: 2 days
Charger: 90 - 260 VAC External Power Supply

Time Base

Standard clock accuracy: 20 ppm (10 min/year
@ - 10 °C to + 50 °C)
External time interfaces: GPS (optional)

Indicators

Green: AC Power LED
Green: Run/Stop LED
Yellow: Event/Memory LED
Red: Warning/Error LED
LCD display: User selectable choice of display parameters

Communication

Serial ports: 2 (1 for communication, 1 for GPS)
Baud rates: 1200, 2400, 4800, 9600, 38400, 57600, 115200
Communication protocol: TG protocol
Protocol securities: Checksum and software handshaking
Communication: PC/RS-232 port or modem
Modem operations: Auto Dial

Environment / Housing

Operational temperature: - 20 °C to + 70 °C
Storage temperature: - 40 °C to + 85 °C
Humidity: 0 % to 100 % (non condensing)
Type: Aluminium housing
Size: 280 x 180 x 100 mm
Weight: 7.2 kg (incl. 6.5 Ah battery)
Protection: IP65 (NEMA 12)

TCP/IP Communication Option

Using a RS-232-TCP/IP device server, **GSR-12/16** can be seamlessly integrated in a TCP/IP computer network for instrument setup and data acquisition. Doing so each **GSR-12/16** can be assigned a unique IP Address.

Self Test

Permanently active, self monitoring and user selectable, periodical system test including comprehensive sensor, memory, filter, real time clock, battery level and hardware tests.

Seismic Switch / Warning Unit Option

The **GSR-12/16** warning option provides two independent warning / error outputs (relay contacts) based on user selectable criteria. This option allows to configure the GSR-12/16 as a seismic switch.

Alarms: 2 relay for 2 alarm levels
1 relay for equipment fault alarm
Alarm levels: 0.1 to 100 % of full scale
(User Programmable per axis)
Relay Hold-On: 1 to 60 seconds
(User Programmable)

GSNet Capabilities

GeoSIG offers various network solutions such as Independent or Interconnected Recording Networks and Local or Central Recording Networks. On-line surveillance, common trigger and time synchronisation are some of the highly advanced functions within the GSNet.